



- Technical Specification:**
1. Valve: High Performance Butterfly
 2. Design STD: EN593
 3. Face to Face: EN558-1 Table 2 Series 20
 4. Flange Connection: EN1092-1(PN10)
 5. Top Flange: ISO5211
 6. Max. W.P. (Bar): 10bar
 7. W.T. Range(°C) : RPTFE(-40~230°C)
 8. Test STD: EN12266-1
- RFQ No.: 1336V.
Order No.:

DN	□E	F	P	H	H1	K1	K2	L	N1	N2	n1xO1	n2xO2	R	s×T	X	M
250	22	25	85	253	230	140	120	68	125	102	4xØ13	4xØ11	350	12xM20	(60)	238.51

POS.No.	ITEM	QTY	PART NAME	MATERIAL	SIZE/DWG.No.	REMARKS/STD.
23	1	0	Assembly	0		
23	1	0	Bracket	S.S.316		
22	4	0	Spring Washer	S.S.316		
21	4	0	Bolt	A4		
20	1	0	Anti-Static Spring	S.S.316L		
19	12	0	Screw	A4		
18	1	0	Bottom Plug	CF8M		
17	1	0	Packing Ring	GRAPHITE		
16	3	0	Distance Ring	S.S. 316L		
15	1	0	Lock Ring	S.S. 316L		
14	2	0	Nut	A4		
13	2	0	Spring Washer	S.S.316		
12	2	0	Stud	A4		
11	1	0	Packing Rester	S.S.316L		
10	4	0	Packing	GRAPHITE		
9-5	1	0	Fire Safe Soft Seat	RPTFE		
9-4	1	0	Fire Safe Seat	S.S. 316L		
9-3	2	0	Graphite Ring	GRAPHITE		
8	2	0	Taper Pin	S31803		
7	1	0	Packing Gland	CF8M		
6	1	0	Packing Sleeve	S.S. 316		
5-2	1	0	Bearing Bush(Down)	S.S. 316L+RPTFE		
5-1	1	0	Bearing Bush(Up)	S.S. 316L+RPTFE		
4	1	0	Shaft	F316L		
3	1	0	Disc	S.S.1.4408		
2	1	0	Seat Ring	CF8M		
1	1	0	Body	S.S.1.4408		



ISSUE REV	DATE	SIGN	DESCRIPTION	APPR. DATE	CHKD	ACCORDING TO ISO-1302	REV.00
03							
02							
01							
00							

DRWN. BY : J.W DATE : 04-01-'24 SIZE DN
 CHKD. BY : M.W DATE : 04-01-'24 A3 250mm
 APPR. BY : S.C DATE : 04-01-'24 DRWG. NO.
 SCALE : SURFACE ROUGHNESS AM:PROJ. 971025002501B
 ACCORDING TO ISO-1302 REV.00