








DETAIL A

Pos	Part name	Material	QTY
1	Body	CF8M	1
2	End Cap	CF8M	2
3	Ball	SS316*	1
4	Seat	CTFE	2
5	Joint Gasket	Graphite	2
6	Thrust Washer	RTFE	1
7	Stem	SS316	1
8	Gland Packing	Graphite	1
8.1	Gland Packing	GLASS FIBER FILLED PTFE	1
9	Gland Bush	SS316	1
10	Stop Washer	SS316	1
11	Stem Nut	SS316	2
12	Handle	SS316	1
13	Handle Cover	Vinyl	1
14	Stem Washer	SS316	1
15	Bolt	SS316	4
16	Bolt Nut	SS316	4
17	Belleville Washer	S301	2
18	Stop Pin	SS316	1
19	Pin Nut	SS316	1
20	Locking Device	SS316	1
21	O-Ring	VITON	1
22	Washer	SS316	1
23	Anti-static Device	SS316	1

S600-1F DN8 - DN50
* 1/4", 3/8" ~ CF8M
1/2", 3/4", 1", 1 1/4", 1 1/2", 2" ~ SS316

KV	Torque (RPTFE)
60 m^3/h	16 nm



 TITLE 3PC BALL VALVE S600-1F 2000PSI 1" BSPP THREAD F-BORE FLOATING CF8M/CF8M/CTFE F04/05 SQR11 FIRESAFE ATEX-IIC W/HANDLE MAR88-1F		NAME	DATE	SIZE	DWG NO		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS AND TOLERANCES ARE +/-0,5
	DRAWN	EMLA	04.01.2024	A3	TRW-100-S600-1F-025		
	CHECKED	EMLA	04.01.2024	FILE NAME: TRW-100-S600-1F-025.dft			
	ENG APPR	TOCO	dd.mm.yyyy	SCALE: 1:2		REV: 00	
	MGR APPR	TOCO	dd.mm.yyyy	WEIGHT: 2.01 kg		SHEET: 1 OF 1	

00	ISSUED	07.02.2024	JOBE
REV	DESCRIPTION	DATE	APPROVED
REVISION HISTORY			