

Fig. 6616, 6626

BALL CHECK VALVE
WITH THREADED END



Technical data:

face to face lenght acc. to drawing
thread connections acc. PN-EN 10226-1:2006
leakproofness class - A
working pressure PN16
medium temperature up to 120°C

Design features:

Total suface rubbered ball.
Drain plug execution possibility. .
All parts are protected against corrosion

Standard execution:
PN16, 70 °C, NBR,
epoxide paint RAL5005 250 µm (*).

Hygienic attest by PZH

Application:

Water lines for sewage, industrial water or other fluids (NBR max.+70° C), and potable water (EPDM max.+120°C)

Figure 6616 for pump installation
Figure 6626 for gravitation installation

Assembly:

Valve can be assembled on pipe line in horizontal or vertical position

*- another executions possibility

No.	Part	Materials
1	Body	eliwo szare, żeliwo sferoidalne EN-GJL-250, PN-EN 1561:2012 EN-GJS-400-15, PN-EN 1563:2012
2	Bonnet	eliwo szare, żeliwo sferoidalne EN-GJL-250, PN-EN 1561:2012 EN-GJS-400-15, PN-EN 1563:2012
3	Ball	Aluminium AISI PN-EN 1706: 2001 Guma NBR, EPDM PN-ISO 1629: 2005
4	Gasket	Guma NBR, EPDM PN-ISO 1629: 2005
5	Screw	stal Fe/Zn5, stal nierdzewna PN-EN ISO 4762: 2006
6	Screw stopper	Parafina
7	Gasket	Guma NBR, EPDM PN-ISO 1629: 2005

DN	G	L	m	H	Weight	
	[cal]	[mm]			6616	6626
					[kg]	
25	1"	120	18	75	1,7	---
32	5/4"	140	18	75	2,2	---
40	6/4"	150	20	89	3,1	---
50	2"	220	35	113	5,0	4,2